

# UniWhite Jointing Compounds

SPARTAN



## Uniwhite

Order Code: UNI

UNIWHITE jointing compound is a white, high-viscosity, paste consisting of a saponified fatty acid, natural minerals, high grade paraffin oils and water. All the substances of the contents are permitted as additives to foodstuffs and the like.

UNIPAK jointing compound applied together with hemp provides 100% tight threaded pipe joints and facilitates connection and future disconnection of the joints. Application of UNIWHITE jointing compound - contrary to e.g. thread seal tape - also provides a large adjusting flexibility as the pipe joints remain tight when loosened.



### Features and benefits

UniWhite is an easily applied non-toxic pipe jointing compound.

Uniwhite jointing compound used in conjunction with hemp is ideal for sealing of threaded pipe joints. It acts as a lubricant to enable pipe threads to be screwed tight. Uniwhite never hardens or leaks. Permits future dismantling of the joints.

UniWhite jointing Compound conforms to BS6956 Part 5 1992 for the use with water, low pressure steam (Max P.S.I 100) Temperature: 140°C/8bar

Uniwhite takes the place of graphite

Uniwhite will not stain

Uniwhite easily wipes off hands without leaving your hands black like graphite.

### Properties

- Non Hardening
- Cures Pliable
- No Leaks
- No Cracks

For Further Information Call Your Plumbing & Gas Equipment Specialists

Aqualine Products 7 Winston Place Henderson Auckland

Phone: (09) 8372725 Fax: (0800) 920700 Email: [sales@aqualine.co.nz](mailto:sales@aqualine.co.nz)

